

# Armstrong Flooring™

## WALLFLEX



**GRUNHAUT** •



Wallflex® es un revestimiento vinílico para paredes de fabricación australiana que ofrece una paleta de diseño refinada y versátil, aportando una estética limpia y sofisticada a cualquier espacio. Creada bajo los conceptos de simplicidad y elegancia, esta colección es la solución ideal para una amplia gama de interiores, incluidos entornos de alta exigencia como hospitales y centros sanitarios, donde la durabilidad y la higiene son fundamentales.

Diseñado para complementar nuestra extensa gama de colecciones de pisos, Wallflex® proporciona una solución continua de pared a suelo que inhibe el crecimiento de moho y bacterias, garantizando un acabado higiénico superior.

Desarrollado para un rendimiento duradero, Wallflex® cuenta con una superficie robusta que resiste arañazos, rozaduras y abolladuras. Esto no solo preserva la apariencia del revestimiento a lo largo del tiempo, sino que también garantiza una solución de bajo mantenimiento y fácil limpieza, siendo especialmente adecuado para áreas donde la pulcritud y la resistencia son esenciales.

## COLORES



**7285 Linen**



**7245 Cool White**



**7275 Blue Harmony**

### Especificaciones generales

- Homogéneo
- 1,25mm de espesor
- 30m<sup>2</sup> por rollo (1,5m de ancho x 20m de largo)

El revestimiento vinílico Wallflex se ha convertido en el estándar australiano para revestimientos de paredes duraderos e higiénicos. Con un diseño limpio y sencillo, Wallflex UBX proporciona un acabado continuo para interiores del sector sanitario que requieren un revestimiento de paredes de larga duración y bajo mantenimiento, capaz de resistir arañazos, rozaduras y abolladuras.

## Technical Data

### Product Classification

Type of floor covering	ISO 10581	Homogeneous sheet vinyl
Wear Class	ISO 10581	Type II
Classification (Use Area)	ISO 10874	Walling only
Warranty*	Commercial - available upon request	15 years

\*All warranties are in addition to any rights consumers may have under Australian and New Zealand consumer laws. Terms and conditions apply - for full information in respect to the scope of the commercial warranty, contact your Armstrong Flooring representative.

### Physical Properties

Manufactured in	–	Australia
Polyurethane reinforced	–	Yes PUR
Colours (Standard)	–	13
Overall thickness	ISO 24346	1.25mm
Roll width	ISO 24341	1.5m
Roll length	ISO 24341	20m
Coverage/roll	–	30.0m <sup>2</sup>
Product weight/m <sup>2</sup>	ISO 23997	3.5kg/m <sup>2</sup>

### Installation

	To current AS/NZS 1884 and Armstrong Flooring Installation Instructions	Full stick, reverse sheets or heat weld seams
--	---	---

### Sustainability

GreenTag GreenRate	–	GreenRate Level A
GreenTag LCARate	–	LCARate Gold
Environmental Product Declaration	–	Yes
Best Environmental Practice PVC	–	Yes
TVOC Emissions	–	Compliant with Green Building Council low VOC emission rates

### Technical Performance

Fire Resistance (Walls) AU	AS 5637.1 Average specific extinction area	Group 1 < 250m <sup>2</sup> /kg
Fire Resistance (Walls) NZ	ISO 5660-1 Average specific extinction area	Group 1-S < 250m <sup>2</sup> /kg
Other		
Colour fastness	ISO 105-B02, Method 3	≥ 6
Residual indentation	ISO 24343-1	≤ 0.1mm (av)
Chemical resistance	–	Good resistance
Flexibility	ISO 24344, Method A	Pass
Seam strength	ISO 16906	Pass

### Accreditation

Manufactured under accredited ISO 9001 quality, ISO 14001 environmental and ISO 45001 OHS management systems

All specifications are current as at date of publication and may be changed without notice. For current and complete specifications please visit [armstrongflooring.au](http://armstrongflooring.au) or [armstrongflooring.co.nz](http://armstrongflooring.co.nz)

All Armstrong Flooring products must be installed in accordance with the relevant Australian and/or New Zealand applicable standards and the Armstrong Flooring Installation Instructions.

Variations may occur between samples, photographic images, and batches in terms of colour, shade, pattern or similar.

**GRUNHAUT** •

# Armstrong Flooring™

## WALLFLEX



+54 9 3512458505



ventas@grunhaut.com



www.grunhaut.com